

FIG. UCH125



Check Wafer Fo/Inox

De hierro, interior de acero inoxidable
Clase 125, ANSI 125/150
Medidas disponibles: 2" – 12"



MATERIALES

Núm.	Nombre	Cant.	Material
1	Cuerpo	1	Hierro A126 Gr. B/AI316
2	Anillo	1	ACERO
3	Eje	1	316/304
4	Resorte	1	316/304
5	Disco	1	WCB/CF8/CF8M
6	Anillo de brida	1	NBR/EPDM/VITON
7	Brida	1	NBR
8	Perno	1	ACERO

UCH125

TAMAÑO	L	ØE	ANSI 125/150
2"	44.5	33	104.8
2 1/2"	47.6	43	123.8
3"	50.8	52	136.5
4"	57.2	76	174.6
5"	63.5	95	196.9
6"	69.9	118	222.3
8"	73	163	279.5
10"	79.4	194	339.8
12"	85.7	241	409.6
14"	108	266	450.9
16"	108	318	514.4

1. Medio:

Agua dulce, agua salada, agua residual, materia alimenticia, vapor, todos los tipos de aceite, etc.

2. Temperatura de operación:

NBR: -10°C ~ +80°C
EPDM: -10°C ~ +120°C
VITON: -20°C ~ +180°C

REQUISITOS TÉCNICOS

- Presión de trabajo: 1.6MPa.
- Pruebas: API598 DIN3230
- Estandar de Bridas: ANSI125/150

